



11803 N Saguaro Blvd | Fountain Hills, AZ 85268

Floor Care Guide

Slide-Lok Garage Floor Coating System

Congratulations! You have purchased one of the finest, longest lasting garage floor coating systems on the market!

Cleaning - Because our system soaks into and bonds with the concrete, Slide-Lok's garage floor coating system is very easy to clean and care for. For normal cleaning, a simple sweep with an ordinary household broom will suffice. When extra cleaning is needed, simply hose down the floor, and using a single or double edge squeegee remove excess water.

In the event you desire to clean up food spills, pet litter or excessive amounts of dirt stains, it is best NOT to use bleach or a citrus or ammonia based detergent. These detergents require good rinsing in order not to leave chemical residue on the floor that can dull or harm the floor with sufficient exposure. A mild biodegradable household cleaner is recommended instead.

In the event that other types of stains accumulate over a period of time such as water leaking from pipes, water heaters or conditioners or wall leakage that leaves mineral deposits then a **diluted solution** of tri sodium phosphate (TSP) can be used to help remove the mineral stains. Again, thoroughly rinse afterwards.

Special Care - Most household chemicals will not damage Slide-Lok's flooring system. Special attention however needs to be given in the event the following chemicals are spilled on your floor:

Battery acid

Brake fluid

Some types of windshield washer

In the event of a spill, simply wipe up the chemical with a dry cloth as quickly as possible, taking care not to get the chemical on your skin or in your eyes. In the event battery acid is spilled on the floor, we recommend applying baking soda to neutralize the acid. Brake fluid and some types of windshield washer, if left on the floor for more than a few hours, may dull the finish of your floor.

Following these simple instructions should give your floor coating system years of service and keep your floor looking like new. In the event of any damage to your Slide-Lok floor coating system, please contact your authorized Slide-Lok dealer for support.

www.slide-lok.com | Phone 480-222-9720 or 800-835-1759 | Fax 480-222-9711

